

## PRODUCT INFORMATION



# AGS 25

Art. No: 3657

## Graffiti remover for rustprotective sealers



**AGS 25 is used for removal of graffiti, made from petroleum based rust protective sealers. AGS 25 is used for removal of graffiti tags and murals on both smooth and porous surfaces. Can be used both externally and internally. On porous surfaces: Use AGS 25 in combination with AGS 27. Readily biodegradable.**

**AGS 25** is a readily biodegradable product used for removal of rust protective sealers.

**AGS 25** may be used on most surfaces: hard non porous surfaces, such as polished stone surfaces, plastic, metal, or porous surfaces such as concrete, brick, granite, plaster, etc.

### INSTRUCTIONS FOR USE

#### Hard non porous surfaces:

When graffiti is spread over an extensive area, use a cloth with **AGS 25**. Neutralise with water.

#### Porous surfaces:

Apply **AGS 25** with low-pressure spray, then apply **AGS 27** with a brush. Products should be allowed to act for 30 minutes - 5 hours, depending on weather conditions. Jet off with high-pressure hot water (70-90°C, approx. 150 bar, nozzle angle 15-25°, 20 litres/ min.). If required repeat the process.

#### Note!

*When cold weather, all graffiti removers need more time to dissolve the graffiti. Like wise more time is required for thick layers and when substrate is porous.*

#### Dosage

Use as concentrate.

#### Consumption

0,5- 1,0 litre/m<sup>2</sup>.

#### Guidelines

- Clear liquid.
- Supplied in 5 litres plastic Jerri cans.
- Specific weight 1,0 kg/litre.
- Faint odour.
- Contains Alcohol ethoxylate and Nitrilotriacetate.

#### Storage

Store frost-free in closed original container.

#### Shelf life

Approximately 24 months in unopened container.

#### Precautions

Use normal protective clothing and gloves.

#### Marking



#### Irritating on eyes and skin

Not classified as dangerous goods in ADR or IMDG.

Modified: 2007-12-21

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and be responsible for the result.

## TRION TENSID AB

Svederusgatan 1-3 | SE-754 50 UPPSALA | SWEDEN Tel: +46 18-15 61 90 Fax: +46 18-69 66 27  
Email: [info@trion.se](mailto:info@trion.se) Homepage: [www.trion.se](http://www.trion.se)