

PRODUCT INFORMATION



AGS 27 GEL

Art. No: 3662

Graffiti remover for rust protective sealers



AGS 27 GEL is used for removal of graffiti, made from petroleum based rust protective sealers. AGS 27 GEL is used for removal of graffiti tags and murals on both smooth and porous surfaces. Can be used both externally and internally. On porous surfaces: Use AGS 27 GEL in combination with AGS 25. Readily biodegradable.

AGS 27 GEL is a readily biodegradable product used for removal of rust protective sealers.

AGS 27 GEL may be used on most surfaces: hard non porous surfaces, such as polished stone surfaces, plastic, metal, or porous surfaces such as concrete, brick, granite, plaster, etc.

INSTRUCTIONS FOR USE:

Graffiti-removal

Smooth surfaces:

When graffiti is spread over an extensive area, apply **AGS 27 GEL** and allow the product to remain on the graffiti for 10-30 minutes, depending on weather conditions, the age of the graffiti and thickness. Jet off with medium pressure, approx. 100 bars, nozzle angle 15-25°, 20 litres/min hot water (60°-90° C).

Porous surfaces:

Apply **AGS 25** with low-pressure spray, then apply **AGS 27 GEL** with a brush. Let dwell for 30 minutes - 5 hours, depending on weather conditions. Jet off with high-pressure hot water (70-90°C, approx. 150 bar, nozzle angle 15-25°, 20 litres/min.). If required repeat the process.

Note!

When cold weather, all graffiti removers need more time to dissolve the graffiti. Like wise more time is required for thick layers and when substrate is porous.

Dosage

Stir and use as concentrate.

Consumption

0,2-0,5 Litres/m².

Guidelines

- Thixotropic light yellow gel.
- Supplied in 5 litres plastic Jerri cans.
- Specific weight 0,87 kg/Litre.
- Faint solvent odour.
- Contains Fatty acids and thickening agent.

Precautions

Use normal protective clothing and gloves.

Marking

No marking is required.

Not classified as dangerous goods in ADR or IMDG.

Storage

Store frost-free in closed original container.

Shelf life

Approximately 24 months in unopened container.

Modified: 2007-12-21

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and be responsible for the result.

TRION TENSID AB

Svederusgatan 1-3 | SE-754 50 UPPSALA | SWEDEN Tel: +46 18-15 61 90 Fax: +46 18-69 66 27

Email: info@trion.se Homepage: www.trion.se