

PRODUCT INFORMATION



AGS 3+ GEL

Art. No: 3650

Graffiti remover for porous surfaces



AGS 3+ is a powerful graffiti and paint remover. For use on exterior and surfaces. AGS 3+ may be used on porous surfaces for all weather conditions. Readily biodegradable.

AGS 3+ GEL is a thickened highly effective graffiti remover to be used on both porous and hard surfaces. **AGS 3+ GEL** dissolves spray-paint graffiti, permanent markers and even petroleum based rust protective sealers.

AGS 3+ GEL may be used on following surfaces:

Porous surfaces

Concrete, brick, granite, marble, limestone, sandstone, slate, surfaces painted with non-organic paint.

Hard surfaces

Metal, treated wood, clinker, glazed brick, glass.

INSTRUCTIONS FOR USE

Graffiti-removal

Apply **AGS 3+ GEL** with a brush or airless sprayer. Agitate the surface well. Leave until graffiti has dissolved, 20 minutes – 4 hours. When cold, the time increases. Jet off with hot water and high pressure, (90°C, 150 bar/2175 PSI). Lance nozzle spread should be 15 - 25 degrees and water flow should be 15 to 20 litres/minute, (4-5 gal/minute).

Note!

For metal surfaces do not use to high pressure.

Instead wipe with sponge or cloth and rinse with warm water.

Dosage

Use as concentrate.

Consumption

0,5 - 1,0 ltr/m².

Technical data

- Viscous bluish fluid.
- Supplied in 5 or 25 ltrs plastic Jerricans.
- Specific weight 0,98 kg/ltr.
- Mild odour.
- Contains gamma-butyrolacton, mixture of aliphatic, naphthenic and aromatic hydrocarbons.

Storage

Store frost-free in original closed container.

Shelf life

Approximately 24 months in un opened container.

Precautions

Protective clothing. Visor when high-pressure washing and breathing mask in poorly ventilated areas.

Marking



HARMFUL

**May cause lung damage if swallowed.
Irritating on eyes and skin.**

Not classified as dangerous goods in ADR or IMDG.

Modified: 2007-09-20

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and be responsible for the result.

TRION TENSID AB

Svederusgatan 1-3 | SE-754 50 UPPSALA | SWEDEN Tel: +46 18-15 61 90 Fax: +46 18-69 66 27
Email: info@trion.se Web: www.trion.se