

PRODUCT INFORMATION



AGS 5 SR

Art. No: 3627

Graffiti remover for hard surfaces



AGS 5 SR is especially developed for removal of shadowing from most types of permanent markers or felt-tip pen graffiti and leather dyes. For use on exteriors and interiors surfaces. AGS 5 SR may be used on most surfaces.

AGS 5 SR effectively removes shadowing from most types of permanent marker or felt-tip pens. Can also be used on spray-paint.

AGS 5 SR may be used on most surfaces; hard non-porous surfaces, such as painted substrates. Porous surfaces, such as concrete, brick, sandstone, limestone, etc.

AGS 5 SR has shown to be very effective to solve difficult leather dye pigments.

INSTRUCTIONS FOR USE

Apply **AGS 5 SR** on to a dry, clean rag or an absorbent paper towel and wipe away the graffiti. Turn over the cloth so that only the clean part is used to the graffiti. Avoid wiping over dissolved graffiti. If there is a grease build up then wipe it off with clean rag. In order to stop the dissolution process, simply apply water on the surface already covered with the graffiti.

It is always recommended a test be made on a small part of the surface.

Dosage

Use as concentrate.

Consumption

0,1-0,3 liter/m².

Technical data

- Brownish yellow liquid.
- Supplied in 5 litre plastic can.
- Specific weight 0,95 kg/litre.
- Solvent odour.
- Flash point >90°C.
- Contains N-Methyl-Pyrrolidon, mixture of aliphatic, naphthenic and aromatic hydrocarbons.

Storage

Store frost-free in closed original container.

Shelf life

Approximately 24 months in unopened container.

Precautions

Use protective clothing, glasses and gloves.

Marking



HARMFUL

May cause lung damage if swallowed.

Not classified as dangerous goods in ADR or IMDG.

Modified: 2007-09-20

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and be responsible for the result.

TRION TENSID AB

Svederusgatan 1-3 | SE-754 50 UPPSALA | SWEDEN Tel: +46 18-15 61 90 Fax: +46 18-69 66 27
Email: info@trion.se Web: www.trion.se