

PRODUCT INFORMATION



AGS 560

Art. No: 3628

For Plexiglass and other delicate surfaces



Graffiti and paint remover. Outside and indoor use. Preferable for hard non-porous surfaces: Especially Plexiglas and other painted surfaces. Biodegradable.

Material

AGS 560 is especially developed for removal of graffiti on Plexiglass. Effectively removes marker felt-tip pen and rust protective coating without attacking the Plexiglas.

AGS 560 is also effective on other painted and delicate surfaces.

AGS 560 even works on spray paint graffiti, but the dissolving time is a little bit longer. Testing on a small surface prior to removal is recommended.

Graffiti removal

Use **AGS 560** on a clean cloth or absorbent paper and wipe off graffiti. Turn the cloth so that the clean part is always used. Avoid smears of dissolved graffiti and wipe off residues of **AGS 560**. Rinse with water and dry with a clean cloth.

The dissolving process is easily interrupted with water.

Dosage

Use as concentrate.

Consumption

0,2 - 0,5 lt/m².

Guidelines

- Yellowish, thinly fluid
- Supplied in 5 litres plastic container or 1 litres plastic bottle.
- Specific weight 0,92 kg/litre.
- Flash point >60°C.
- Mild odour.
- Contains: 2-(2-butoxyethoxy)ethanol.

Storage

Store frost-free in closed original container.

Shelf life

Approximately 24 months in unopened container.

Precautions

Safety gloves, safety glasses in case of splashes.

Marking



Irritating to eyes

Not classified as dangerous goods in ADR or IMDG.

Modified: 2007-12-21

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and be responsible for the result.

TRION TENSID AB

Svederusgatan 1-3 | SE-754 50 UPPSALA | SWEDEN Tel: +46 18-15 61 90 Fax: +46 18-69 66 27

Email: info@trion.se Web: www.trion.se