

## PRODUCT INFORMATION



# AGS 60

Art. No: 3660

## Graffiti- shadow remover



**AGS 60 is used for removal of graffiti-shadows in conjunction with graffiti removal. Readily biodegradable according to OECD test 302 b. For use on exterior and interior surfaces. Primarily used on absorbent surfaces.**

### INSTRUCTIONS FOR USE

**AGS 60** removes shadowing left in substrate following graffiti removal, in special cases also paint removal.

**AGS 60** is formulated for use on the following materials; granite, slate, sand-stone, glazed brick, treated marble, wood and non-organic paint.

**AGS 60** must not be used on soft metal surfaces, aluminium, for example.

### Graffiti-shadow removal

Apply **AGS 60** by brush on wet surface, leave to act for 2 - 30 minutes until graffiti/shadowing has dissolved. Jet off with high pressure hot water, (40-90°C, 70-150 bar/1015-2175 PSI). Adjust pressure to suit surface condition.

Note! For metal surfaces; the effectiveness can be reduced if too high pressure is used. A better result can be achieved if the surface is wiped with a sponge or cloth in the rinsing process. Repeat the procedure if required.

*NB! Do not use AGS 60 on aluminium.*

### Dosage

Use concentrate.

### Consumption

0,2 - 0,5 Lt/m<sup>2</sup> per application using concentrate.

### Guidelines

- Yellow/brownish slight viscous fluid.
- Supplied in 5 or 25 lt. plastic Jerricans.
- Specific weight 1,06 kg/Lt.
- pH-value approx. 14.
- Contains Potassium hydroxide and surfactants.

### Storage

Store frost-free in closed original container.

### Shelf life

Approximately 24 months in unopened container.

### Precautions

Special caution must be taken, as **AGS 60** is a corrosive product. Use protective clothing, visor, glasses and gloves.

If product comes in contact with eyes, rinse with lot of water and immediately to hospital.

If skin contact, rinse with lot of water, to hospital if necessary.

### Marking



### CORROSIVE

Classified as dangerous goods in road and sea transport. UN 1814

Modified: 2007-12-21

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and be responsible for the result.

## TRION TENSID AB

Svederugatan 1-3 | SE-754 50 UPPSALA | SWEDEN Tel: +46 18-15 61 90 Fax: +46 18-69 66 27

Email: [info@trion.se](mailto:info@trion.se) Homepage: [www.trion.se](http://www.trion.se)