



# AGS-Graffiti Control & Cleaning Rolling Stock



# Removal of exterior graffiti

## Painted surfaces



Be careful when removing graffiti from delicate surfaces such as plastic foil.

### Painted surfaces

#### Spray paint

AGS 221 GEL

- Apply a thick layer of AGS 221 GEL with a brush.
- Cover all graffiti and wait 5-15 minutes.
- Agitate with a brush until the graffiti is dissolved.
- Jet off with a high pressure cleaner, 80-120 bars and 70°C .
- If required, repeat the process.

#### Ink & Felt Tip pen

AGS 5 SR

- Use AGS 5 SR on a clean cloth or highly absorbing paper and wipe off the graffiti.
- Turn the cloth so that the clean side is always used.  
*If necessary use a white scotch Brite.*
- Neutralize with water.
- Wipe the surface dry with a clean cloth.

#### Rust protective sealers

- When the graffiti is spread over an extensive area, apply AGS 27 GEL with a brush.
- Wait for 5–15 minutes, agitate with the brush until the graffiti is dissolved.
- Jet off with a high pressure cleaner, 80-120 bars and 70°C .
- In case of tags and small spots of graffiti: Use AGS 27 liquid on a cloth and wipe off.
- Neutralize with water.

# Protection and removal of graffiti

## Gangway bellows



### Gangway bellows

#### PROTECTED WITH AGS 3502/3512

(2 LAYERS ACC. TO OUR INSTRUCTIONS)

- Outdoors: Jet off with a high pressure cleaner, 70–100 bars and 90° C
- Indoors: Use AGS 3505 on a clean cloth or highly absorbing paper and wipe off the graffiti.
- Re-apply twice with AGS 3502/3512.

#### IF UNPROTECTED USE AGS 221 LIQUID/AGS 27 LIQUID

- Use the same method as for painted surfaces but use AGS 221 liquid and AGS 27 liquid (avoid AGS 5SR)

# Removal of Graffiti from interior surfaces

## Panels, Windows, Floors & Seats



### Panels & Windows

#### Ink/Felt Tip pen/Spray

- Use AGS 5 SR or AGS 5 SR GEL on a clean cloth or absorbing paper and wipe off the graffiti
- Turn the cloth so the clean side is always used
- Neutralize with water and wipe the surface dry with a clean cloth
- NB! With remaining shadows: Use AGS 5 SR Gel, let dwell for 15-45 minutes. Agitate with a brush.
- Neutralize with water and wipe the surface with a clean cloth.
- If necessary use a white scotch Brite.

### Floors

*Pre-treat the floor with BPS 7750, 2 times let dry 1 hour between the layers. Apply with a low pressure spray See data sheet for instructions.*

#### Ink/felt tip pen/Spray

- Use AGS 5 SR or AGS 221 liquid on a clean cloth or absorbing paper and wipe off the graffiti
- Turn the cloth so the clean side is always used. Work towards the middle
- Neutralize with water and wipe the surface dry with a clean cloth.

*In case of difficulties: Apply Reno 212 and then add AGS 221 liquid. Work with a white Scotch Brite. Neutralize with water.*

### Seats

#### Spray & Ink/Felt tip pen

- Soak the attacked area with AGS 5 SR .
- Leave to work for a few minutes.
- Use a clean cloth to absorb the graffiti.
- Neutralize the surface with SPEEDY or an alkali multipurpose cleaner

# Removal of graffiti from interior surfaces

## Doors



### Doors

#### Ink/Felt Tip pen/Spray

- Use AGS 5 SR on a clean cloth or highly absorbing paper and wipe off the graffiti
- Turn the cloth so the clean side is always used. Work towards the middle.
- Neutralize with water or a window cleaner and wipe the surface dry with a clean cloth.
- **Very difficult cases**, e.g.. Ink/leather dye or ghostings, apply AGS 5 SR GEL with a brush, leave for 15–45 minutes.
- Agitate the surface with a white scotch Brite.
- Wipe the surface with a clean cloth or highly absorbing paper. Work towards the middle.
- Neutralize with water and wipe the surface dry with a clean cloth.

#### Prevent with permanent coating.

- Protect with e.g. AGS Tutoprom. Follow instructions on data sheet.

#### Graffiti removal on Tutoprom

##### AGS 560/221 liquid/5 SR

- Apply the remover with clean cloth or absorbing paper and wipe off the graffiti.
- Always use a clean part of the cloth/paper
- Neutralize with water and wipe until dry.

# Removal of Graffiti from interior surfaces

## Drivers Cab door & panel



### Drivers Cab doors & Panel

#### Ink/Felt Tip pen/Spray

AGS 5 SR

- Use AGS 5 SR on a clean cloth or absorbing paper and wipe off the graffiti
- Turn the cloth so the clean side is always used. Work towards the middle
- Neutralize with water and wipe the surface dry with a clean cloth

*Ghostings and leather dyes follow instructions on page 5*

#### Prevent with permanent coating.

- Protect with e.g. AGS Tutoprom. Follow instructions on data sheet.

#### Graffiti removal on Tutoprom

##### AGS 560/221 liquid/5 SR

- Apply the remover with clean cloth or absorbing paper and wipe off the graffiti.
- Always use a clean part of the cloth/paper
- Neutralize with water and wipe until dry.

# Daily cleaning of interior surfaces

## Floor, Panel & Windows



### Floor & Panel

#### TCS 25

- Use TCS 25 Universal cleaner. Effective cleaning agent of dirt, soot and grease.
- Dilute with water.

Dilution Ratio

Light cleaning: 1:50

Normal cleaning: 1:10

Heavy cleaning: 1:5

### Windows

#### Window Cleaner

- Use Trion Tensid WINDOW CLEANER. Does not leave any watermarks.
- Apply with a trigger spray and wipe off with a clean, soft cloth.

# Cleaning of exterior surfaces



## Daily wash

### TCS 25 alkaline

Dilution ratio

Normal automatic cleaning 1:50

Extra cleaning 1:10

Heavy cleaning 1:5

## Removal of oxides

### TCS Railcleaner

To be used in concentrate



trion tensid ab

Trion Tensid AB  
Svederusgatan 1-3  
SE-754 50 Uppsala, Sweden  
Tel: +46 (0) 18 15 61 90  
Fax: + 46 (0) 18 69 66 27  
info@trion.se  
www.trion.se